

**Technical Data**  
Contains 1, 1, 1-trichloroethane  
(71-55-6), Isopropanol (67-63-0),  
ethanol (64-17-5), carbon dioxide  
(124-38-9) Meets MIL-1-81223  
Fed. Spec. TT-1-735 and 01520  
Type III Nonflammable Class  
TWA 350 ppm

**For Industrial Use Only**  
**Caution:** Do not puncture, inhale  
or store above 120°F (50°C).  
Exposure to heat may cause  
bursting. Contact with open flame  
or other very hot surfaces can  
cause vapor decomposition and  
toxic gases. Vapor heavier than  
air and will displace oxygen and  
is not suitable for breathing. Use only with  
adequate ventilation. Avoid breathing  
vapor.

**Suggested First Aid:** Eye Contact:  
Immediately flush eyes with  
plenty of water for 10 minutes. Call  
a physician. Skin Contact: Wash  
with soap and water. Inhalation:  
Provide fresh air. Ingestion: Do not  
induce vomiting. Call a physician.

**Note:** Use only as directed. See  
label for more information. This  
product is not for use in food processing  
and other food contact applications.  
Keep out of reach of children.

**Chemtronics Inc.**  
Northbrook, IL 60062 USA  
404-424-8888 © 1992

PANEL MOUNT

SMA BARREL

ALBERTO

RED



Common Industrial Torq Meters  
Fibre Visual Fault Locator for Fibre  
Local Layer Distance Meter  
GAUSS METER

DESIGNER'S TOOL KITS